

# MATERIAL DATA SHEET

KOVAX EUROPE B.V.

Getfertweg 290-4  
7512 BG Enschede  
The Netherlands

Tel: +31 (0) 53 - 434 31 31  
Fax: +31 (0) 53 - 430 49 00

DATE REVISED: January 01, 2008

## I. GENERAL INFORMATION

PRODUCT: Buflex pads stick-on

PART#: 971-0012, 971-0014

### CHEMICAL NAME & SYNONYMS:

Material, Binding System

### CHEMICAL FAMILY:

N/A

### PROPER DOT SHIPPING NAME:

N/A

### TRADE NAME & SYNONYMS:

Buflex pads stick-on

### FORMULA:

N/A

### DOT HAZARD CLASSIFICATION:

Not Restricted

## II. INGREDIENTS

CHEMICAL NAME	%	COMMON NAME	REG.	CAS.#	THRESHOLD LIMIT VALUE (UNITS)	CARCINOGEN
Material	90	Urethane Foam	N			N
Binding System	10	Mixture	N			N

## III. PHYSICAL DATA

BOILING POINT: (F) N/A	SPECIFIC GRAVITY: (H <sub>2</sub> O = 1) N/A
VAPOR PRESSURE: (mm Hg.) N/A	PERCENT VOLATILE BY VOLUME: (%) N/A
VAPOR DENSITY: (Air = 1) N/A	EVAPORATION RATE: ( = 1) N/A
SOLUBILITY IN WATER: N/A	ph: N/A
APPEARANCE & ODOR: Urethane Foam Pad	

## IV. FIRE & EXPLOSION HAZARD DATA

FLASH POINT (TEST METHOD): N/A

AUTO IGNITION TEMPERATURE: N/A

LEL: N/A

UEL: N/A

FLAMMABLE LIMITS: N/A

EXTINGUISHING MEDIA: N/A

SPECIAL FIRE FIGHTING PROCEDURES: Use respiratory protection.

UNUSUAL FIRE & EXPLOSION HAZARDS: Urethane foam will burn or decompose.

## V. HEALTH HAZARD DATA

**PRODUCT: Buflex pads stick-on**  
**PART# : 971-0012, 971-0014**

<b>Threshold Value:</b> N/A	<b>OSHA Threshold Limit Value:</b> N/A	<b>ACGIH Threshold Limit Value:</b> N/A
<b>Carcinogen - NTP Program:</b> N/A	<b>Carcinogen -IARC Program:</b> N/A	
<b>SYMPTOMS OF EXPOSURE:</b> Coughing, shortness of breath, chronic dust may effect breathing capacity. May cause skin abrasion, eye irritation. <b>Medical Conditions Aggravated by Exposure:</b> N/A <b>Primary Routes of Entry:</b> Inhalation, Ingestion, Skin, Eye <b>EMERGENCY FIRST AID:</b> INHALATION: Remove to fresh air, apply artificial respiration as needed. Obtain first aid or medical assistance. INGESTION: Obtain first aid or medical assistance if needed. SKIN: Obtain first aid or medical assistance if needed. EYE: Wash with large amounts of water obtain first aid or medical assistance if needed.		

## VI. REACTIVITY DATA

<b>STABILITY:</b> Stable	<b>CONDITIONS TO AVOID:</b> N/A
<b>INCOMPATIBILITY:</b> N/A	<b>MATERIALS TO AVOID:</b> N/A
<b>HAZARDOUS POLYMERIZATION:</b> N/A	<b>CONDITIONS TO AVOID:</b> N/A
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b> In use dust and decomposing resin system fumes are generated.	

## VII. ENVIRONMENTAL PROTECTION PROCEDURE

<b>SPILL RESPONSE:</b> Normal clean up procedure.
<b>WASTE DISPOSAL METHOD:</b> Standard landfill methods consistant with applicable federal, state & local laws.

## VIII. SPECIAL PROTECTION INFORMATION

<b>EYE PROTECTION:</b> Recommended	<b>SKIN PROTECTION:</b> Gloves if desired.
<b>RESPIRATORY PROTECTION:</b> As needed, approved dust respirator	<b>VENTILATION RECOMMENDED:</b> LOCAL: recommended MECHANICAL: recommended OTHER: NAIF
<b>OTHER PROTECTION:</b> Measure to be taken during repair and maintenance of contaminated equipment that has been contact with this material: SEE Section VI, VII, VIII.	

## IX. SPECIAL PRECAUTIONS

<b>HYGENIC PRACTICES IN HANDLING &amp; STORAGE:</b> Handle with adequate ventilation.
<b>PRECAUTIONS FOR REPAIR &amp; MAINTENANCE OF CONTAMINATED EQUIPMENT:</b> N/A
<b>OTHER PRECAUTIONS:</b> N/A

## X. PRODUCT APPLICATION

**PRODUCT: Buflex pads stick-on**

**PART# : 971-0012, 971-0014**

**FIELD OF APPLICATION:** Automotive, industry, yacht building

**PRODUCT APPLICATION:** The Buflex pads are used in combination with Buflec stick-on discs and sheets.

Purpose: to remove contamination and imperfections in the clear coat and prepare the surface for polishing.

**USAGE INSTRUCTION:**

- **SHEETS:** Use Buflex pad 971-0012 in combination with stick-on Buflex sheets green (191-1502) and black (191-1501).
- **DISCS:** Use Buflex pad 971-0014 in combination with stick-on Buflex discs green (192-1502) and black (192-1501).

**REMARK:** It is important to work according to the usage instruction. It describes the right combination of pads and sanding paper, with which you will obtain the optimal sanding result.

When sanding with Buflex, a small amount of water is required.

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.