

MATERIAL DATA SHEET

KOVAX EUROPE B.V.

Getfertweg 290-4
7512 BG Enschede
The Netherlands

Tel: +31 (0) 53 - 434 31 31
Fax: +31 (0) 53 - 430 49 00

DATE REVISED: January 01, 2008

I. GENERAL INFORMATION

PRODUCT: Buflex Green Mini Super-Tack Discs
PART# : 730-1503

CHEMICAL NAME & SYNONYMS:

Grain, Backing, Binding System, Nylon pile

CHEMICAL FAMILY:

N/A

PROPER DOT SHIPPING NAME:

N/A

TRADE NAME & SYNONYMS:

Buflex Green Mini Super-Tack Discs

FORMULA:

N/A

DOT HAZARD CLASSIFICATION:

Not Restricted

II. INGREDIENTS

CHEMICAL NAME	%	COMMON NAME	REG.	CAS. #	THRESHOLD LIMIT VALUE (UNITS)	CARCINOGEN
Grain	30	Aluminium Oxide	N	1344-28-1	15mg/m ³ OSHA, 10mg/m ³ ACGIH	N
Backing	35	Urethane Resin	N			N
Binding System	30	Mixture	N			N
Velour	5	Nylon Pile	N			N

III. PHYSICAL DATA

BOILING POINT: (F) N/A	SPECIFIC GRAVITY: (H₂O = 1) N/A
VAPOR PRESSURE: (mm Hg.) N/A	PERCENT VOLATILE BY VOLUME: (%) N/A
VAPOR DENSITY: (Air = 1) N/A	EVAPORATION RATE: (= 1) N/A
SOLUBILITY IN WATER: N/A	ph: N/A
APPEARANCE & ODOR: Film coated with abrasive materials.	

IV. FIRE & EXPLOSION HAZARD DATA

FLASH POINT (TEST METHOD): N/A
AUTO IGNITION TEMPERATURE: N/A
LEL: N/A
UEL: N/A
FLAMMABLE LIMITS: N/A
EXTINGUISHING MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: Use respiratory protection.
UNUSUAL FIRE & EXPLOSION HAZARDS: Backing & resin will burn or decompose.

V. HEALTH HAZARD DATA

PRODUCT: Buflex Green Mini Super-Tack Discs

PART# : 730-1503

Threshold Value:

N/A

OSHA Threshold Limit Value:

N/A

ACGIH Threshold Limit Value:

N/A

Carcinogen - NTP Program:

N/A

Carcinogen -IARC Program:

N/A

SYMPTOMS OF EXPOSURE:

Coughing, shortness of breath, chronic dust may effect breathing capacity.

Not absorbed trough skin but may cause abrasion, eye irritation.

OTHER POTENTIAL HEALTH RISK:

During use on some materials, elevated sound levels may affect hearing.

Medical Conditions Aggravated by Exposure: N/A

Primary Routes of Entry: Inhalation, Ingestion, Skin, Eye

EMERGENCY FIRST AID:

INHALATION: Remove to fresh air, apply artificial respiration as needed. Obtain first aid or medical assistance.

INGESTION: Obtain first aid or medical assistance if needed. **SKIN:** Obtain first aid or medical assistance if needed.

EYE: Wash with large amounts of water obtain first aid or medical assistance if needed.

VI. REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: N/A

INCOMPATIBILITY: N/A

MATERIALS TO AVOID: N/A

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: N/A

HAZARDOUS DECOMPOSITION PRODUCTS: In use dust and decomposing resin system fumes are generated.

VII. ENVIRONMENTAL PROTECTION PROCEDURE

SPILL RESPONSE: Normal clean up procedure.

WASTE DISPOSAL METHOD: Standard landfill methods consistant with applicable federal, state & local laws.

VIII. SPECIAL PROTECTION INFORMATION

EYE PROTECTION: Recommended

SKIN PROTECTION: Gloves if desired.

RESPIRATORY PROTECTION:

VENTILATION RECOMMENDED: LOCAL: recommended

As needed, approved dust respirator

MECHANICAL: recommended

OTHER PROTECTION:

OTHER: NAIF

Measure to be taken during repair and maintenance of contaminated equipment that has been contact with this material: SEE Section VI, VII, VIII.

IX. SPECIAL PRECAUTIONS

HYGENIC PRACTICES IN HANDLING & STORAGE: N/A.

PRECAUTIONS FOR REPAIR & MAINTENANCE OF CONTAMINATED EQUIPMENT: N/A

OTHER PRECAUTIONS: N/A

X. PRODUCT APPLICATION

PRODUCT: Buflex Green Mini Super-Tack Discs

PART# : 730-1503

GRIT: +/- P2500-P3000

FIELD OF APPLICATION: Automotive, industry, yacht building

PRODUCT APPLICATION: Removal of contamination and imperfections in the clear coat. For a perfect finish.

USAGE INSTRUCTION:

- After using Tolex, start sanding with Buflex green (+/- P2500)
- Finish with Buflex black (+/- P3000)
- For the best polishing result, we advise to use our coarse rubbing compound followed by the ultrafine rubbing compound (for both light and dark colours).

REMARK: The Buflex discs 75 mm are typical spot repair products. It is a wet sanding system, which requires only a small amount of water. Use the added pads for usage with the mini dual action sander. Use our coarse rubbing compound in combination with our yellow foam pad (858-6791) and the ultrafine rubbing compound in combination with our black foam pad (858-6793).

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.