

MATERIAL DATA SHEET

KOVAX EUROPE B.V.

Getfertweg 290-4
7512 BG Enschede
The Netherlands

Tel: +31 (0) 53 - 434 31 31
Fax: +31 (0) 53 - 430 49 00

DATE REVISED: January 01, 2008

I. GENERAL INFORMATION

PRODUCT: Mini Super-Tack Discs 75 mm
PART# : 730-0060 to 730-0600

CHEMICAL NAME & SYNONYMS:

Grain, Backing, Binding System, Anti-clog System, Nylon pile

CHEMICAL FAMILY:

N/A

PROPER DOT SHIPPING NAME:

N/A

TRADE NAME & SYNONYMS:

Mini Super-Tack Discs 75 mm

FORMULA:

N/A

DOT HAZARD CLASSIFICATION:

Not Restricted

II. INGREDIENTS

CHEMICAL NAME	%	COMMON NAME	REG.	CAS. #	THRESHOLD LIMIT VALUE (UNITS)	CARCINOGEN
Grain	35	Silicone Carbide	N	1344-28-1	15mg/m ³ OSHA, 10mg/m ³ ACGIH	N
Backing	30	Paper Latexed	N			N
Binding System	25	Mixture	N			N
Anti-Clog System	5	Stearic Acide	N	1592-23-0		N
Velour	5	Nylon Pile	N			N

III. PHYSICAL DATA

BOILING POINT: (F) N/A	SPECIFIC GRAVITY: (H₂O = 1) N/A
VAPOR PRESSURE: (mm Hg.) N/A	PERCENT VOLATILE BY VOLUME: (%) N/A
VAPOR DENSITY: (Air = 1) N/A	EVAPORATION RATE: (= 1) N/A
SOLUBILITY IN WATER: N/A	ph: N/A
APPEARANCE & ODOR: Film coated with abrasive materials.	

IV. FIRE & EXPLOSION HAZARD DATA

FLASH POINT (TEST METHOD): N/A
AUTO IGNITION TEMPERATURE: N/A
LEL: N/A
UEL: N/A
FLAMMABLE LIMITS: N/A
EXTINGUISHING MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: Use respiratory protection.
UNUSUAL FIRE & EXPLOSION HAZARDS: Backing & resin will burn or decompose.

V. HEALTH HAZARD DATA

PRODUCT: Mini Super-Tack Discs 75 mm
PART# : 730-0060 to 730-0600

Threshold Value: N/A	OSHA Threshold Limit Value: N/A	ACGIH Threshold Limit Value: N/A
Carcinogen - NTP Program: N/A	Carcinogen -IARC Program: N/A	

SYMPTOMS OF EXPOSURE:
Coughing, shortness of breath, chronic dust may effect breathing capacity.
Not absorbed trough skin but may cause abrasion, eye irritation.

OTHER POTENTIAL HEALTH RISK:
During use on some materials, elevated sound levels may affect hearing.

Medical Conditions Aggravated by Exposure: N/A
Primary Routes of Entry: Inhalation, Ingestion, Skin, Eye

EMERGENCY FIRST AID:
INHALATION: Remove to fresh air, apply artificial respiration as needed. Obtain first aid or medical assistance.
INGESTION: Obtain first aid or medical assistance if needed. SKIN: Obtain first aid or medical assistance if needed.
EYE: Wash with large amounts of water obtain first aid or medical assistance if needed.

VI. REACTIVITY DATA

STABILITY: Stable	CONDITIONS TO AVOID: N/A
INCOMPATIBILITY: N/A	MATERIALS TO AVOID: N/A
HAZARDOUS POLYMERIZATION: Will not occur.	CONDITIONS TO AVOID: N/A

HAZARDOUS DECOMPOSITION PRODUCTS: In use dust and decomposing resin system fumes are generated.

VII. ENVIRONMENTAL PROTECTION PROCEDURE

SPILL RESPONSE: Normal clean up procedure.

WASTE DISPOSAL METHOD: Standard landfill methods consistant with applicable federal, state & local laws.

VIII. SPECIAL PROTECTION INFORMATION

EYE PROTECTION: Recommended	SKIN PROTECTION: Gloves if desired.
RESPIRATORY PROTECTION: As needed, approved dust respirator	VENTILATION RECOMMENDED: LOCAL: recommended MECHANICAL: recommended OTHER: NAIF
OTHER PROTECTION: Measure to be taken during repair and maintenance of contaminated equipment that has been contact with this material: SEE Section VI, VII, VIII.	

IX. SPECIAL PRECAUTIONS

HYGENIC PRACTICES IN HANDLING & STORAGE: N/A.

PRECAUTIONS FOR REPAIR & MAINTENANCE OF CONTAMINATED EQUIPMENT: N/A

OTHER PRECAUTIONS: N/A

X. PRODUCT APPLICATION

PRODUCT: Mini Super-Tack Discs 75 mm
PART# : 730-0060 to 730-0600

GRIT: P60-P600

FIELD OF APPLICATION: Automotive

PRODUCT APPLICATION: To be used for spot repair sanding and polishing purposes.

USAGE INSTRUCTION:

- Remove paint and/or oxidation (+/- P60 - +/-P150)
- Sand the putty (+/- P60 - +/-P150)
- Reduce sanding scratches (+/- P150 - +/- P320)
- Bring on the primer
- Further reduce sanding scratches (+/- P320-P360)
- Scuff the old paint, sand the sides and the filler (+/- P500)
- Spray the new paint

Continue the sanding process with the following steps:

- Sand the edges for bringing on the clear coat (+/- P800 - P1500)
- Use Yellow film for further reduction of sanding scratches (+/- P800 - P1500)
- Removing final scratches and/or imperfections with Tolex (+/- P2000)
- Use Buflex green (+/- P2500) and black (+/- P3000) for a perfect finish

REMARK: To be used in combination with pad (M75-0148) for mini dual action sander (910-7501).
Use also the interfacepad (971-7502) from grit P800 and finer.

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.