

MATERIAL DATA SHEET

KOVAX EUROPE B.V.

Getfertweg 290-4
7512 BG Enschede
The Netherlands

Tel: +31 (0) 53 - 434 31 31
Fax: +31 (0) 53 - 430 49 00

DATE REVISED: January 01, 2008

I. GENERAL INFORMATION

PRODUCT: Touch-Up Stickon Discs
PART#: 880-2000

CHEMICAL NAME & SYNONYMS:

Grain, Backing, Binding System

CHEMICAL FAMILY:

N/A

PROPER DOT SHIPPING NAME:

N/A

TRADE NAME & SYNONYMS:

Touch-Up Stickon Discs

FORMULA:

N/A

DOT HAZARD CLASSIFICATION:

Not Restricted

II. INGREDIENTS

CHEMICAL NAME	%	COMMON NAME	REG.	CAS. #	THRESHOLD LIMIT VALUE (UNITS)	CARCINOGEN
Grain	40	Silicon Carbide	N	409-21-2	15mg/m ³ OSHA, 10mg/m ³ ACGIH	N
Backing	30	Paper, Latexed	N			N
Binding System	30	Mixture	N			N

III. PHYSICAL DATA

BOILING POINT: (F) N/A	SPECIFIC GRAVITY: (H ₂ O = 1) N/A
VAPOR PRESSURE: (mm Hg.) N/A	PERCENT VOLATILE BY VOLUME: (%) N/A
VAPOR DENSITY: (Air = 1) N/A	EVAPORATION RATE: (= 1) N/A
SOLUBILITY IN WATER: N/A	ph: N/A
APPEARANCE & ODOR: Paper coated with abrasive material	

IV. FIRE & EXPLOSION HAZARD DATA

FLASH POINT (TEST METHOD): N/A
AUTO IGNITION TEMPERATURE: N/A
LEL: N/A
UEL: N/A
FLAMMABLE LIMITS: N/A
EXTINGUISHING MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: Use respiratory protection.
UNUSUAL FIRE & EXPLOSION HAZARDS: Backing & resin will burn or decompose.

V. HEALTH HAZARD DATA

PRODUCT: Touch-Up Stickon Discs
PART# : 880-2000

Threshold Value: N/A	OSHA Threshold Limit Value: N/A	ACGIH Threshold Limit Value: N/A
Carcinogen - NTP Program: N/A	Carcinogen -IARC Program: N/A	
SYMPTOMS OF EXPOSURE: Coughing, shortness of breath, chronic dust may effect breathing capacity. May cause skin abrasion, eye irritation. Medical Conditions Aggravated by Exposure: N/A Primary Routes of Entry: Inhalation, Ingestion, Skin, Eye EMERGENCY FIRST AID: INHALATION: Remove to fresh air, apply artificial respiration as needed. obtain first aid or medical assistance. INGESTION: Obtain first aid or medical assistance if needed. SKIN: Obtain first aid or medical assistance if needed. EYE: Wash with large amounts of water obtain first aid or medical assistance if needed.		

VI. REACTIVITY DATA

STABILITY: Stable	CONDITIONS TO AVOID: N/A
INCOMPATIBILITY: N/A	MATERIALS TO AVOID: N/A
HAZARDOUS POLYMERIZATION: Will not occur.	CONDITIONS TO AVOID: N/A
HAZARDOUS DECOMPOSITION PRODUCTS: In use dust and decomposing resin system fumes are generated.	

VII. ENVIRONMENTAL PROTECTION PROCEDURE

SPILL RESPONSE: Normal clean up procedure.
WASTE DISPOSAL METHOD: Standard landfill methods consistant with applicable federal, state & local laws.

VIII. SPECIAL PROTECTION INFORMATION

EYE PROTECTION: Recommended	SKIN PROTECTION: Gloves if desired.
RESPIRATORY PROTECTION: As needed, approved dust respirator	VENTILATION RECOMMENDED: LOCAL: recommended MECHANICAL: recommended OTHER: NAIF
OTHER PROTECTION: Measure to be taken during repair and maintenance of contaminated equipment that has been contact with this material: SEE Section VI, VII, VIII.	

IX. SPECIAL PRECAUTIONS

HYGENIC PRACTICES IN HANDLING & STORAGE: Handle with adequate ventilation.
PRECAUTIONS FOR REPAIR & MAINTENANCE OF CONTAMINATED EQUIPMENT: N/A
OTHER PRECAUTIONS: N/A

X. PRODUCT APPLICATION

PRODUCT: Touch-Up Stickon Discs
PART# : 880-2000

GRIT: +/- P2000

FIELD OF APPLICATION:Automotive, Industry, Yacht Building

PRODUCT APPLICATION:For touch-up sanding and polishing. Only for wet application.

USAGE INSTRUCTION:

- Bring on the clear coat
- Remove the final sanding scratches and imperfections with waterproof touch-up
- For a perfect end result, use Buflex green (+/- P2500) and black (+/- P3000) for polishing

REMARK:

- To be used in combination with interface pad for touch-up sander.

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.